PROCESS STAGE 3 OF 6 · KNEAD

Rubber Dispersion Kneader

VIK-25-110 · 45-250 L

The Rubber Dispersion Kneader mixes and kneads rubber compounds to a uniform dispersion, which is critical for consistent product quality. Temperature control and easy hydraulic-tilt discharge keep batches moving, even on the most demanding production schedules.



Efficient mixing blades
Uniform dispersion of fillers and chemicals.

Temperature control
Hold the compound in its working window.

Robust construction
Built for continuous, multi-shift production.

Easy material discharge
Hydraulic tilting empties the chamber fast.

Dispersion kneader models

Model	Main motor	Rotor speed	Chamber volume (L)	Working capacity	Tilting angle (°)	Tilting power pack (HP)	Hydraulic system
VIK-25	40	22/31	45	25	120–130	3	5
VIK-35	60	27/31	75	35	120–130	5	5
VIK-55	75/100	27/31	125	55	120–130	5	5
VIK-75	100/125	27/31	170	75	120–130	5	5
VIK-110	200	27/31	250	120	120–130	7.5	5

Specifications are a starting point. Every machine is configured to your compound, product and line layout. Send us your requirement for a configured specification and written quote.

Call or WhatsApp
+91 99204 84368
info@vikasindustriesmachinery.com

Factory
Plot No. 46, Dewan & Sons, Udyog Nagar, Village Allayali, Palghar (West), Palghar 401 404

Web
vikasindustriesmachinery.com
Family-run since 1995 · ISO 9001:2015